

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (currently amended) A method for delivering ~~certificates with associated trust~~ information from a trust information provider to a client for verification of a received certificate by said client, comprising the steps of:
  - providing a trust information object (TIO) to said client, wherein; and
  - ~~providing as part of said TIO~~ comprises: 1) a hash value of a trust entity certificate, and 2) associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate, wherein the trusted entity comprises a certificate authority; and
  - verifying a received certificate using at least a portion of said TIO.
2. (original) The method of Claim 1, wherein said TIO comprises any of:
  - a trusted entity's certificate;
  - a trust vector of said trusted entity's certificate;
  - a value indicating a number of signatures required for a next update;
  - a date said TIO is created; and
  - a digital signature of all data including said certificate, trust vector, number of signatures, and timestamp, contained in said TIO.
3. (original) The method of Claim 1 wherein said hash value is determined using any of MD5 and SHA-1.
4. (previously presented) The method of Claim 1, wherein said TIO conforms to the PKCS#7 standard.
5. (previously presented) The method of Claim 1, further comprising the step of:
  - hard coding a TIO derived from a set of root certificate authority (CA) certificates into said client's software.

6. (original) The method of Claim 1, further comprising the step of:  
    saving a copy of said TIO in a persistent memory during said client's build time.
7. (withdrawn) A method for delivering certificates with associated trust information from a server to a client for verification of a received certificate by said client, comprising the steps of:  
    associating a trust information object (TIO) with said client, said TIO comprising a hash value of a trust entity certificate and associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate;  
    during an SSL handshake between said client and said server, said server sending a certificate chain that, optionally, contains a root certificate (RC) to said client; and  
    said client validating said server certificate using said TIO.
8. (withdrawn) The method of Claim 7, wherein said client hashes a server certificate and compares a resulting digest against a list of trusted entity certificate thumbprints obtained from said TIO.
9. (withdrawn) The method of Claim 8, wherein if a thumbprint match is not found:  
    said client retrieves an RC from a trusted server;  
    said client performs certificate chain validation up to a root certificate authority (CA);  
    once an entire certificate chain is validated, said client tries to validate said CA RC;  
    wherein, if said RC is included in said certificate chain, said client hashes said RC and looks up said TIO in said client;

wherein if a resulting hash value and a corresponding trust bit are found in said TIO, then said certificate chain is considered to be valid and session initiation proceeds.

10. (withdrawn) The method of Claim 8, wherein if a thumbprint match is, said client checks a trust bit vector associated with said certificate to ensure that an authenticated server is trusted in the context of a session being established.

11. (withdrawn) The method of Claim 9, wherein if necessary trust capabilities are not set on a matched thumbprint, said client fails a session initiation handshake.

12. (withdrawn) The method of Claim 7, wherein a hash value in said TIO is taken by hashing a valid certificate; and wherein said certificate is accepted by a validation mechanism, even when said client receives an expired root certificate.

13. (withdrawn) The method of Claim 7, further comprising the step of:  
providing in said TIO a designated trust bit associated with a site certificate for identifying a site that is trusted to perform certain operations;  
wherein when said client executes a script it checks said certificate and associated trust information; and  
wherein if said trust bit indicates that a site identified by its certificate is trusted for an intended operation, then access permission is granted.

14. (currently amended) A method for delivering ~~certificates with associated trust information from a server to a client for verification of a received certificate by said client~~, comprising the steps of:  
embedding a trust information object (TIO) within said client, said TIO comprising: 1) a hash value of a trust entity certificate, and 2) associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate, wherein the trusted entity comprises a certificate authority;

said client connecting to said server to determine whether a new TIO is available; and

said server sending a new TIO to said client if there is a more recent TIO.

15. (previously presented) The method of Claim 14, further comprising the step of:  
sending a TIO including a signing certificate to said client, wherein trust information of said signing certificate indicates that said signing certificate can be trusted for signing said TIO.

16. (original) The method of Claim 14, wherein said client fetches said TIO from a trusted server, said client ensuring that a root certificate that signed said signing certificate is contained in said TIO and is not revocable.

17. (previously presented) The method of Claim 14, wherein said client verifies a digital signature of said TIO with a signing certificate along with a TIO sent to said client.

18. (original) The method of Claim 17, wherein multiple signatures are verified, depending on the number of signatures specified in said TIO; wherein said client hashes said signing certificates one by one; and wherein if proper results are found in said TIO and said certificates are trusted for signing said TIO, then said TIO proves that it was not tampered with.

19. (original) The method of Claim 18, wherein said signing certificates exist in said TIO in said client before said TIO is signed.

20. (currently amended) The method of Claim 14, wherein said TIO is delivered to said client via a broadcast channel;

wherein a provider delivers an initial TIO to said client that contains a signing certificate and associated trust information by either of including said signing certificate in the said initial TIO saved in a client persistent memory, or by sending

said initial TIO to said client through a secure channel before using said broadcast channel.

21. (original) The method of Claim 14, further comprising the step of:  
updating said TIO on a per session basis when said TIO is not persistently stored.

22. (currently amended) An apparatus for receiving ~~certificates with associated trust~~ information from a server for verification of a received certificate, comprising:

a client device for receiving a trust information object (TIO) associated with said client device, wherein[[;]]

said TIO ~~comprising~~ comprises: 1) a hash value of a trust entity certificate, and 2) associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate, wherein the trusted entity comprises a certificate authority;

wherein said client device is adapted for verifying a received certificate using at least a portion of said TIO.

23. (Cancelled)

24. (original) The apparatus of Claim 22, said TIO comprising any of:

a time stamp which indicates a date that said TIO is generated;

a trust attribute that comprises trust information associated with an entity represented by its certificate; and

a thumb print comprising a hash of a public key embedded in a certificate that represents a trusted entity.

25. (currently amended) An apparatus for receiving ~~certificates with associated trust~~ information from a trust information provider for verification of a received certificate, comprising:-

a client device for receiving a trust information object (TIO) associated with said client device[[:]]

wherein said TIO includes: 1) a hash value of a trust entity certificate, and 2) associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate, wherein the trusted entity comprises a certificate authority;

wherein said client device is adapted for verifying a received certificate using at least a portion of said TIO.

26. (previously presented) The apparatus of Claim 25, wherein said TIO comprises any of:

- a trusted entity's certificate;
- a trust vector of said trusted entity's certificate;
- a value indicating a number of signatures required for a next update;
- a date said TIO is created; and
- a digital signature of all data including said certificate, trust vector, number of signatures and timestamp, contained in said TIO.

27. (previously presented) The apparatus of Claim 25, wherein said hash value is determined using any of MD5 and SHA-1.

28. (previously presented) The apparatus of Claim 25, wherein said TIO conforms to the PKCS#7 standard.

29. (currently amended) The apparatus of Claim 25, wherein said TIO comprises a TIO derived from a set of root certificate authority (CA) certificates hard coded into ~~said client's software~~ of said client device.

30. (currently amended) The apparatus of Claim 25, wherein said TIO further comprises:

a copy of said TIO saved in a persistent memory during said client's client device's build time.

31. (withdrawn) An apparatus for delivering certificates with associated trust information from a server to a client for verification of a received certificate by said client, comprising:

a trust information object (TIO) associated with said client, said TIO comprising a hash value of a trust entity certificate and associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate;

means for sending a certificate chain from said server that, optionally, contains a root certificate (RC) to said client during an SSL handshake between said client and said server; and

means at said client for validating said server certificate using said TIO.

32. (withdrawn) The apparatus of Claim 31, wherein said client hashes a server certificate and compares a resulting digest against a list of trusted entity certificate thumbprints obtained from said TIO.

33. (withdrawn) The apparatus of Claim 32, wherein if a thumbprint match is not found:

said client retrieves an RC from a trusted server;

said client performs certificate chain validation up to a root certificate authority (CA);

once an entire certificate chain is validated, said client tries to validate said CA RC;

wherein, if said RC is included in said certificate chain, said client hashes said RC and looks up said TIO in said client;

wherein if a resulting hash value and a corresponding trust bit are found in said TIO, then said certificate chain is considered to be valid and session initiation proceeds.

34. (withdrawn) The apparatus of Claim 32, wherein if a thumbprint match is, said client checks a trust bit vector associated with said certificate to ensure that an authenticated server is trusted in the context of a session being established.

35. (withdrawn) The apparatus of Claim 34, wherein if necessary trust capabilities are not set on a matched thumbprint, said client fails a session initiation handshake.

36. (withdrawn) The apparatus of Claim 31, wherein a hash value in said TIO is taken by hashing a valid certificate; and wherein said certificate is accepted by a validation mechanism, even when said client receives an expired root certificate.

37. (withdrawn) The apparatus of Claim 31, further comprising:

a designated trust bit in said TIO associated with a site certificate for identifying a site that is trusted to perform certain operations;

wherein when said client executes a script it checks said certificate and associated trust information; and

wherein if said trust bit indicates that a site identified by its certificate is trusted for an intended operation, then access permission is granted.

38. (currently amended) An apparatus for delivering ~~certificates with associated trust information from a server to a client for verification of a received certificate by said client~~, comprising:

a client device having embedded therein a trust information object (TIO) comprising: 1) a hash value of a trust entity certificate, and 2) associated trust information indicating a level of trust for a trusted entity associated with said trust entity certificate, wherein the trusted entity comprises a certificate authority;



wherein said client device connects to said server to determine whether a new TIO is available; and

wherein said server sends a new TIO to said client if there is a more recent TIO.

39. (currently amended) The apparatus of Claim 38, wherein a trusted server sends a TIO including a signing certificate to said client device, wherein trust information of said signing certificate indicates that said certificate can be trusted for signing said TIO.

40. (currently amended) The apparatus of Claim 38, wherein said client device fetches said TIO from a trusted server, said client device ensuring that a root certificate that signed said signing certificate is contained in said TIO and is not revocable.

41. (currently amended) The apparatus of Claim 38, wherein said client device verifies a digital signature of said TIO with a signing certificate along with a TIO sent to said client device.

42. (currently amended) The apparatus of Claim 41, wherein multiple signatures are verified, depending on the number of signatures specified in said TIO; wherein said client device hashes said signing certificates one by one; and wherein if proper results are found in said TIO and said certificates are trusted for signing said TIO, said client device utilizes said TIO.

43. (currently amended) The apparatus of Claim 42, wherein said signing certificates exist in said TIO in said client device before said TIO is signed.

44. (currently amended) The apparatus of Claim 38, wherein said TIO is delivered to said client device via a broadcast channel;

wherein a provider delivers a TIO to said client device that contains a signing certificate and associated trust information by either of including said signing certificate in an initial TIO saved in a client persistent memory, or by sending said TIO to said client through a secure channel before using said broadcast channel.

45. (currently amended) The apparatus of Claim 38, wherein said client device updates said TIO on a per session basis when said TIO is not persistently stored.

46. (currently amended) A method for delivering ~~certificates with associated trust~~ information from a server to a client for verification of a received certificate by said client, comprising the steps of:

receiving a trust information object (TIO) at said client, wherein:  
~~providing within~~ said TIO comprises: 1) a hash value of a trust entity  
certificate, and 2) associated trust information indicating a level of trust for a trusted  
entity associated with said trust entity certificate, wherein the trusted entity  
comprises a certificate authority; and  
verifying a received certificate using at least a portion of said TIO.

47. (Cancelled)

48. (original) The method of Claim 46, said TIO comprising any of:

a time stamp which indicates a date that said TIO is generated;  
a trust attribute that comprises trust information associated with an entity represented by its certificate; and  
a thumb print comprising a hash of a public key embedded in a certificate that represents a trusted entity.

49. (currently amended) A method for delivering ~~certificates with associated trust~~ information from a trust information provider to a client for verification of a received certificate by said client, comprising the steps of:

providing a trust information object (TIO) to said client, wherein; and  
~~providing as part of said TIO comprises:~~ 1) a hash value of a public key  
embedded in a certificate that represents a trusted entity, and 2) trust information  
indicating a level of trust for the trusted entity associated with said certificate,  
wherein the trusted entity comprises a certificate authority; and  
verifying a received certificate using at least a portion of said TIO.